Top 10 Consumables Tech Tips



Maintain a quality edge finish
 ▶Replace carbide cutters every 300 cycles
 Disposable Carbide Cutter - Bevel 5mm Shelf (NOP-93072) 10/pkg



Optimize bevel placement calculation

▶Replace probe tips when they are not sharp at the tip

Probe Tips (NOP-27092) Each



Prevent crazing, scratches and slippage

►Change taper plugs at first signs of wear


Taper Plugs (NOP-90178, 17mm, 6/pkg and NOP-73162 19mm, Each)



4 Extend wheel life and give better quality polish when clean water makes contact with the wheels

► Change the sponge when prompted as well as vacuum them nightly. Replace if damaged, shredded or misshapen

Sponges (NOP-29104) 10/pkg



Prevent the vacuum motor from having to work harder to pull through debris and burn through brushes prematurely and damaging the motor life ▶ Change your vacuum bags when the bag is 75% full Vacuum Bags Set (NOP-90140) 25/pkg



6 Prevent slippage and axis issues

▶Test your right side clamp (RSC) by running the axis burn-in without load for 10 passes, and then run it with the calibration disk clamped for 10 passes. If you see a jump in the Average Power, the RSC should be changed.

Right Side Clamp (NOP-90043 19mm, NOP-90083 17mm) Each



Prevent slippage, axis issues, crazing and bad bevels

►Only use high quality edging pads within one year of their manufacture date Edging Pads (BluEdge and HydroEdge – Different shapes and sizes)



8 Prevent slippage, axis issues, crazing and bad bevels

► Check edging blocks for signs of wear and indentation and replace as needed Edging Blocks (DV2001-1400 24mm round, DV2001-1401 18mm half eye) 25/pkg



9 Prevent debris from clogging solenoid or manifold

►Clean or replace water filter on the water bottle. ALWAYS use distilled water to prevent mineral build-up
Filter Element (NOP-75158) Each



10 Proper blade movement and edger sizing

► Check cutter clamp for wear. If you see indentation, replace it.

Polishing Cutter Clamp (NOP-93148) Each